

## NRL4

R-4 

### FOR USE ON BACKHOE LOADERS IN NUMEROUS WORKING CONDITIONS

- **Classical directional lug tread pattern and open shoulder groove design**

Benefit: Improved traction and self-cleaning capability on the pavement, soft soil and dirt, as well as in mud.

- **Massive lugs reinforced by a centerline tread rubber belt, robust casing**

Benefit: Increased resistance to impact.

- **Available in multiple tread compounds**

Benefit: Compounds available for both standard and severe working conditions.



Size	Ply Rating	TRA Code	Rim	Dimension		Load Capacity 10km/h	Inflation Pressure 10km/h	Tread Depth (mm)	Type
				Section width(mm)	Overall diameter(mm)				
18.4-26	12	R-4	DW16	467	1450	2985	230	33.5	TL
18.4-26	14	R-4	DW16	467	1450	3320	280	33.5	TL
14.5/75-20	12	R-4	12	372	1060	3155	320	26.5	TL
14.5/75-20	14	R-4	12	372	1060	3460	370	26.5	TL
12.5/80-18	12	R-4	9	308	985	2625	370	25	TL
12.5/80-18	14	R-4	9	308	985	2910	430	25	TL
12.5/80-18	16	R-4	9	308	985	3130	490	25	TL